





















9402












9402N

NR	ELEMENT	9402N
E1		1
E2		1
E3		1
E4		1
E5		1
E6		1



NR	ELEMENT	9402N
E7		1
E8		1
E9		1
E10		1
E11		1
E12		1

NR	ELEMENT	9402N
E13		1
E14		4
E15		2
E16		13
E17		1
E18		1

NR	ELEMENT	9402N
E19		1
E20		1
E21		1
E22		1
E23		1
E24		1

NR	ELEMENT	9402N
E25		2
E26		1
E27		1

9402N




9402N

A= 70cm
B= 80cm

"0"



Technical drawing of the 9402N machine, showing a side view of the machine and a top view of the base. The side view shows a vertical shaft with a handle and a base. The top view shows a rectangular base with dimensions A=70cm and B=80cm. The detailed view shows a complex arrangement of pipes, valves, and a ladder, with numerous dimensions and labels.

"0"





1

9402N





2

9402N





3

9402N





4

9402N




5


9402N




9402N




B25 1,8m³




min. 48H



Nr	Σ	Element		
58	-		-	LOCTITE




A (1 : 2)




Nr. 5

F


Nr	Σ	Element	DIN	ELEMENT
61	2		-	KL105







B (1 : 5)




INST_94_0_1




Nr 24

Nr	Σ	Element		
90	4		DIN 125	16x30
164	2		DIN 985	M16
229	4		-	Z_R_42
230	2		-	S1_8100_0


1




2












3





INST_94_1




Nr	Σ	Element		
58	1		-	LOCTITE





Nr	Σ	Element		
58	1		-	LOCTITE





1






2





Nr	Σ	Element	DIN	ELEMENT
58	1		-	LOCTITE





1



2





Nr	Σ	Element		
58	1		-	LOCTITE





1


2



3





Nr	Σ	Element		
58	1		-	LOCTITE





1




2






3



Nr	Σ	Element		
58	1		-	LOCTITE




1




2




I






II




III







I





II






III







INST_94_30N

Nr	Σ	Element		
1	2		-	S6x60
2	2		-	W6x60



INST_Z_1

Nr	Σ	Element		
213	1		-	Z_NA_1
214	1		-	Z_NA_2



Conservation and control of the Product

According to the PN EN 1176-1 : 2017-12-Norm

The conservation and exploitation:

It is required to consult with the Manufacturer about all maintaining works of the Products' parts which are under guarantee.

The anticorrosive surface:

Damaged paint coat should be first cleaned out of dust, fat and corrosion centres. After that, the cleaned surface should be covered with an anticorrosive primer for steel surfaces. When the layer is dry, paint twice with spray paint.

The colour combination used by BUGLO according to the RAL palette:

Grey – RAL 7035, Yellow – RAL 1003, Blue – RAL 5015, Red – RAL 3000, Green – RAL 6018, Black – RAL 9005, Purple – RAL 4008, Anthracite – RAL 7016, Silver – RAL 9006, Beige – RAL 1019, Orange – RAL 2009, Brown - RAL 8017

Wood:

Elements made of glued laminated timber require a regular renovation. Depending on climate conditions, level of exploitation and mechanical damages, it is advised to renew the impregnation layer after a period of 2 – 5 years. Before finishing, timber elements need to be mattified, then following products need to be applied:

- 1) Impregnating Foundation – GORI 356
- 2) Surface paint – NORDICA EKO 3330 – 12TM1806

Products are available via distribution network of Teknos Company (www.teknos.com). Usage according to the producer's instructions.

IROKO wood: preserve with Owatrol D1.

Stainless steel:

It is recommended to clean stainless steel elements once a year, to remove sediments and contaminants, which accumulation can cause steel discolouring. Wash with cotton cloths and gentle detergent dissolved in water, eg. dishwashing liquid. After cleaning rinse with water and wipe dry.

Caution!

Cleaners used to clean stainless steel **must not** contain: chlorine, salt, acids or bleaches. Even small amount of these substances can cause permanent damage of chromium oxide surface.

Recommendations for the product control according to the EN 1176-7: 2020-Norm Playground equipment and the surfaces part 7: Guidelines for the assembly, control, conservation and exploitation/running.

1) Post-installation inspection – recommended before the playground opens for public use to assess the access to the product and its surroundings taking into consideration overall security level.

2) The periodic control – if the product is used very intensively or is exposed to vandalism, the control should be carried out once a week or more frequently.

The periodic control includes:

- potential damage of any elements,
- tightening of the connectors,
- outer coat of the set,
- condition of the shock-absorbing surface,
- bearing lubrication,
- completeness of the products,
- checking if there are no cracks, sharp edges or other damages,
- the cleanness around the Product (broken glass determines a big danger) and smoothing the safety surface,
- the presence of obstacles in the safe space or fall space and their removal if present,
- general safety status of the playground.

3) The functional control – should be carried out once every three months.

It includes the range of the periodic inspection enlarged by examining the product's functions.

- during the functional control the fixed elements of the product should be checked (completeness of caps and masking elements),
- checking the stability of the posts,
- checking the loose-fill safety surface (eg. sand, gravel, bark, woodchips) and evening it out. If the level is under 10cm below the marked surface level, it must be filled in,
- tighten all screws,
- checking the tensions of the zip line rope, nets and rope pyramids,
- checking of the condition of welds,
- replacing of worn or damaged elements.

4) The functional control and the main control – mandatory once a year.

The main control covers:

- checking the construction's stability,
- checking and reconstructing the anti-corrosion coating that was damaged,
- checking the foundation's condition,
- checking the loose-fill safety surface (eg. sand, gravel, bark, woodchips) and evening it out. If the level is under 10cm below the marked surface level, it must be filled in,
- checking the condition of wooden elements, if included.

The equipment should have a regular check-up control by competent people (with certified level of competence).

Every time the check-up control takes place, the playground administrator should record it on inspection sheets. Any modifications of the equipment or design that may affect the basic safety of the equipment should be carried out after consultation with the manufacturer or a competent person.

All personnel involved in playground safety management must be competent.

Full range of requirements according to EN 1176-7:2020.

A sample of playground inspection sheet is included in attachment A1.

Control sheet of the playground



Administrator of the playground

Controlled equipment (product number, manufacturer number)

Check-up plan

Check-up run once a week or more often, depends on how intensively the product is used (periodically)		YES	NO
1	General condition of the safety on the playground.		
2	Tightening of the connectors, bearings lubrication, checking of the shock-absorbing surface.		
3	Is the set complete?		
4	Are there any cracks, sharp edges or other damages in the device?		
5	Is the area surrounding the device clean (no glass, safe surface horizontal/even)?		
6	Are there any obstacles in the clear space or fall space?		

Check-up run once in a three months (functional)		YES	NO
1	Are the non-separable elements complete (covers and masking elements are complete)?		
2	Are the posts stable?		
3	Is the loose safe surface horizontal/even?		
4	Is the level of the safety surface up to the marked level or is max. 10cm below this level?		
5	Is the condition of the connectors adequate?		
6	Is the condition of the welds adequate?		
7	Are the ropes and nets tensioned correctly?		
8	Replacing of worn or damaged elements.		

Check-up run once a year (functional an main)		YES	NO
1	Is the construction stable?		
2	Are there any damages to the anticorrosional coat?		
3	Is the powdery safe surface horizontal/even?		
4	Is the condition of the foundation adequate?		
5	Is the condition of wooden elements adequate?		
6	Is the level of the safety surface up to the marked level or is max. 10cm below this level?		

Fault/Repair

1	
2	
3	
4	
5	

Parts exchange

	Name of the part	Qty	Reason
1			
2			
3			

Date	Inspector's name
1	
2	
3	
4	